

20k - 60k MP AND HP TUBING

15k

20k

30k

60k

TUBING

TOOLS

SPARE
PARTS

Cold draw thick wall seamless tubing

From 1379 to 4137 bar (20,000 to 60,000 psi)

Material

Temperature range

-252°C to +649°C
(-421°F to +1200°F)

External surface finish

Bright finish, free from lumps,
flaws and fissures

Inner surface finish

Minimum 100 RMS = 2,3 Ra µm
= 92 AARH

Tolerance

OD and ID: ±0,1 mm
WT: ±10%

Standard


6 meters (20 feet)
Also available in different lengths
upon request

Certification

EN 10204 3,1
Eddy current ASTM A450/E426

Description

Cold drawn thick wall seamless
tubing for fluid or gas high-
pressures applications such
as hydraulic, test equipment,
waterjet and water-cutting



DTE - MP and HP tubing

Part No	UM	OD	ID	Thickness	WP	Length	Weight
DTE04A600AB01	mm	6,35	2,79	1,78	1379 bar	6 m	0,202 Kg/m
	in.	1/4"	0.11"	0.070"	20.000 psi	19.685 ft	0.136 lbs/ft
DTE06C600AB01	mm	9,53	5,17	2,18	1379 bar	6 m	0,397 Kg/m
	in.	3/8"	0.20"	0.086"	20.000 psi	19.685 ft	0.267 lbs/ft
DTE09E600AB01	mm	14,29	7,94	3,18	1379 bar	6 m	0,877 Kg/m
	in.	9/16"	0.31"	0.125"	20.000 psi	19.685 ft	0.589 lbs/ft
DTE12F600AB01	mm	19,1	11,18	3,96	1379 bar	6 m	1,487 Kg/m
	in.	3/4"	0.44"	0.156"	20.000 psi	19.685 ft	0.999 lbs/ft
DTE16G600AB01	mm	25,4	14,28	5,56	1379 bar	6 m	2,736 Kg/m
	in.	1"	0.56"	0.219"	20.000 psi	19.685 ft	1.839 lbs/ft
DTH04B600AB01	mm	6,35	2,13	2,11	4137 bar	6 m	0,222 Kg/m
	in.	1/4"	0.08"	0.083"	60.000 psi	19.685 ft	0.149 lbs/ft
DTH06E600AB01	mm	9,53	3,17	3,18	4137 bar	6 m	0,501 Kg/m
	in.	3/8"	0.12"	0.125"	60.000 psi	19.685 ft	0.337 lbs/ft
DTH09D600AB01	mm	14,29	4,74	4,78	4137 bar	6 m	1,129 Kg/m
	in.	9/16"	0.19"	0.187"	60.000 psi	19.685 ft	0.759 lbs/ft